





Male Connector on PCB

1. VCC(DC5V)
2. Phase A+
3. Phase A-
4. Phase B+
5. Phase B-
6. Phase Z+
7. Phase Z-
8. GND

(Unit:mm)

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
Bluencoder(Suzhou) Technology Co.Ltd. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
Bluencoder(Suzhou) Technology Co.Ltd IS
PROHIBITED.





Magnetic Encoder IC

Other Components

Plug Radially

Optional holder dia.

Magnet Holder




Optional Length:
1m/1.5m/2m



This PCB form fact main Spec.:
All Temperatur Range is -40deg~+125deg
1. Incremental resolution 1024~4096PPR
2. A+/A- B+/B- Z+/Z- differential output

Max. Speed is 10,000 RPM



		DIMENSIONS ARE IN MM
		TOLERANCES: ±0.1
		FRACTIONAL ±
		ANGULAR: MACH ± BEND ±
		TWO PLACE DECIMAL ±
		THREE PLACE DECIMAL ±
		MATERIAL --
		FINISH --
NEXT ASSY	USED ON	
APPLICATION	DO NOT SCALE DRAWING	

	NAME	DATE
DRAWN		
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		
EI28S06		

Blue encoder(Suzhou)



Embedded
Incremental
Encoder

SIZE A	DWG. NO.	REV. v1.0
SCALE:	WEIGHT:	SHEET OF